

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Patent Abstracts of Japan

PUBLICATION NUMBER : 58025081
 PUBLICATION DATE : 15-02-83


APPLICATION DATE : 05-08-81
 APPLICATION NUMBER : 56122667

APPLICANT : FURUKAWA BATTERY CO LTD:THE;

INVENTOR : HIRATA JUNICHI;

INT.CL. : H01M 4/24

TITLE : ELECTRODE PLATE FOR STORAGE BATTERY



ABSTRACT : PURPOSE: To increase adhesion of an active mass to an electrode plate by applying the mixture obtained by mixing powder or particle zinc, short fibers, and a binder on a punched metal substrate, and press-fixing zinc active mass on its outside.

CONSTITUTION: Both sides of a nickel plated iron punched metal substrate 1 are coated with the mixture formed by mixing powder or particle zinc, short fibers, and a binder such as PVA, CMC, and dried to form a mixture layer 2. A zinc active mass layer 3 is fixed by applying pressure with a press on the outside of the mixture layer 2 to form the electrode plate for a storage battery. This electrode plate has many advantages such as no falling off of zinc active mass, long life, and low cost.

COPYRIGHT: (C)1983,JPO&Japio